



Duco Ducoweb

Quality printing for all web applications

The Ducoweb blanket is suitable for use on all Heatset and Coldset web presses. Its micro ground surface gives class leading print quality on coated and uncoated stocks.

Ducoweb's low stretch, high strength, waterproof carcass provides maximum stability and minimal gauge loss, ensuring extended lifetime. The advanced compressible layer gives excellent smash resistance, reduced vibration and ensures no blanket/edge marking for consistent performance.

Features	Benefits	Specifications
Micro ground surface.	Gives exceptional print quality on a wide range of stocks.	Colour: Blue
High quality stabilising fabric.	Minimal gauge loss at bevel.	Surface: Micro ground
Thick compressible layer.	High smash resistance, absorbs vibration.	Thickness: 1.95mm, 1.70mm
Dense, low stretch, waterproof fabric.	Minimal gauge loss, high strength and stability, maximum lifetime.	Hardness: 75° Shore A
		Compressibility: 0.15mm @ 1060 kPa Typical (1.95) 0.21mm @ 2060 kPa Typical (1.95) 0.16mm @ 1060 kPa Typical (1.70) 0.23mm @ 2060 kPa Typical (1.70)
		Elongation: <0.50% @ 10 N/mm
		Tensile Strength: >75 N/mm
		Face Compound: Solvent resistant rubber blend

Optimise your on-press performance

Over the years, Day's printing technologists and pressroom chemists have learned the dynamics between printing blankets, inks and pressroom chemicals play a vital role in on-press performance and profitability. And they've learned how to analyse these dynamics to help printers resolve problems and optimise their printing results.

Day's laboratory experts, technical support team and sales consultants work together with printers to recommend the right combination of pressroom products to achieve optimum performance. A consultative service offered only by Day International.



Day International -
Eastbourne Road, Slough,
Berkshire, SL1 4SF,
England.

T +44 (0)1753 522274
F +44 (0)1753 691952
E day.uk@flintgrp.com
www.flintgrp.com