

# **UltraCURA Base**

Base colour ink series optimised for the usage on paper and board

UV base colour ink series for sheetfed offset

#### **Product Features**

- UltraCURA Base is a highly reactive UV base colour ink series for sheetfed presses.
- It is suitable for commercial application on paper and board.
- The series consists of 13 base colour inks as well as black, transparent and opaque white. Base colours have high colour strength, optimised to blend spot colours.

### **Advantages of UltraCURA Base**

- Fast work turnaround.
- Good rub resistance.
- High colour strength.
- · Very good ink-water stability.
- Fast curing speed.
- Reduced energy consumption.
- Ideally suited for paper and board.



## **UltraCURA Base**

		Fastness properties			
		Light fastness	hol	Solvent mixture	=
	Article code	Ligh	Alcoho	Solv	Alkali
UltraCURA					
Yellow	VW26-100*	5	+	+	+
G/S Yellow	VW26-111*	6	+	+	+
Orange	VW26-200*	5	+	+	+
Warm Red	VW26-300*	3	+	+	+
Red 032	VW26-302*	5	+	-	+
Rubine Red	VW26-301*	5	+	+	-
Rhodamine Red	VW26-303*	5	-	-	-
Purple	VW26-400*	4	-	-	-
Violet	VW26-401*	4	-	-	-
Process Blue	VW26-500*	8	+	+	+
Blue 072	VW26-572*	4	-	-	-
Reflex Blue	VW26-501*	3	-	-	+
Green	VW26-600*	8	+	+	+
Transparent White	VW26-000*	Not applicable			
Opaque White	VW26-001*	Not applicable			
Black	VW26-960*	8 + + +			
UltraCURA Fast					
Resistant G/S Yellow	VW18-190*	7	+	+	+
Resistant R/S Yellow	VW18-189*	7	+	+	+
Resistant Orange	VW18-211*	6	+	+	+
Y/S Red	VW18-355*	7	+	+	+
Resistant Rubine Red	VW18-366*	7	+	+	+
Resistant Rhodamine Red	VW18-369*	7	+	+	+
Resistant Violet	VW18-450*	7	+	+	+
Resistant Reflex Blue	VW18-508*	7	+	+	+
		Light fastness properties according to ISO 12040: from 1 (low) to 8 (high)  Fastness properties according to ISO 2836: + = Resistance provided - = Resistance not provided			

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

\* Depending on the producing site

### **UltraCURA Base**

Substrates Ideally suited for coated and uncoated paper and board.

Hints for the mixing of spot colours

Thanks to their high colour strength and mono-pigmentation, UltraCURA Base colour inks feature very easy formulation and mixing of spot colours; also true when specific resistance requirements are specified. Furthermore it is possible to achieve all colour shades of the PANTONE® range with the typical film weight usually applied in wet offset printing. Therefore

formulations for coated paper must be chosen.

Remarks UltraCURA Base inks are suitable for printing with or without alcohol.

UltraCURA Base inks have been formulated to exclude materials known to cause swelling or degradation of EPDM and NBR type rollers and blankets. In general, UV curable inks and the special cleaning fluids can, to a certain extent, cause swelling or shrinking of rubbers. Rubber

types like EPDM, butyl nitrile or vinyl nitrile are recommended.

**Shelf life and storage** The recommended storage temperature is 5 - 35 ° C.

Direct sunlight as well as long-term exposure to fluorescent lamps should be avoided to prevent polymerisation. Meeting the recommended storage conditions, UltraCURA Base will remain stable

for a minimum of 12 months from the date of manufacture.

**Exceptions** Not for use for food packages without functional barrier.

### More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

### Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.